

# Stafford

## METRIC RIGID SHAFT COUPLINGS TWO-PIECE SPLIT CLAMP-TYPE

- Fully metric, including clamp screws
- Mate two shafts with zero backlash
- Two pieces for convenient assembly and adjustment
- Smooth bore protects shafts from damage
- Superior torque capacity over set-screw-type couplings



Stafford Metric Rigid Shaft Couplings are fully metric in all specifications, including the clamping screws.

Designed for aligned shafts, the 2-Piece Clamp-Type Coupling makes two shafts function as one. This coupling comes completely apart to allow the most convenient assembly and adjustment. It is ideal for overhung or unsupported shafts and is an excellent way to attach items such as mixer paddles and shaft extensions.

Metric Clamp-Type Couplings are available in straight-through bores. They are precision machined, non-marring, easy to adjust, with high clamping power.

Stocked in:

- Steel
- Stainless Steel

1 2

<u>Part Number</u>	<u>Bore Size A</u>	<u>Bore Size B</u>	<u>Material</u>	<u>Type</u>	<u>Outside Diameter</u>	<u>Total Length</u>
<a href="#">5SM006006E</a>	6 mm	6 mm	Stainless Steel	Low Profile	16 mm	30 mm
<a href="#">5LM006006E</a>	6 mm	6 mm	Steel	Low Profile	16 mm	30 mm
<a href="#">5SM008008E</a>	8 mm	8 mm	Stainless Steel	Low Profile	18 mm	30 mm
<a href="#">5LM008008E</a>	8 mm	8 mm	Steel	Low Profile	18 mm	30 mm
<a href="#">5SM009009E</a>	9 mm	9 mm	Stainless Steel	Low Profile	24 mm	35 mm
<a href="#">5LM009009E</a>	9 mm	9 mm	Steel	Low Profile	24 mm	35 mm
<a href="#">5SM010010E</a>	10 mm	10 mm	Stainless Steel	Low Profile	24 mm	35 mm
<a href="#">5LM010010E</a>	10 mm	10 mm	Steel	Low Profile	24 mm	35 mm
<a href="#">5SM012012E</a>	12 mm	12 mm	Stainless Steel	Low Profile	28 mm	45 mm

<u>Part Number</u>	<u>Bore Size A</u>	<u>Bore Size B</u>	<u>Material</u>	<u>Type</u>	<u>Outside Diameter</u>	<u>Total Length</u>
<a href="#">5LM012012F</a>	12 mm	12 mm	Steel	Low Profile	28 mm	45 mm
<a href="#">5SM014014F</a>	14 mm	14 mm	Stainless Steel	Low Profile	30 mm	50 mm
<a href="#">5LM014014F</a>	14 mm	14 mm	Steel	Low Profile	30 mm	50 mm
<a href="#">5SM015015F</a>	15 mm	15 mm	Stainless Steel	Low Profile	34 mm	50 mm
<a href="#">5LM015015F</a>	15 mm	15 mm	Steel	Low Profile	34 mm	50 mm
<a href="#">5SM016016F</a>	16 mm	16 mm	Stainless Steel	Low Profile	34 mm	50 mm
<a href="#">5LM016016F</a>	16 mm	16 mm	Steel	Low Profile	34 mm	50 mm
<a href="#">5SM018018F</a>	18 mm	18 mm	Stainless Steel	Low Profile	36 mm	60 mm
<a href="#">5LM018018F</a>	18 mm	18 mm	Steel	Low Profile	36 mm	60 mm
<a href="#">5SM020020F</a>	20 mm	20 mm	Stainless Steel	Low Profile	40 mm	65 mm
<a href="#">5LM020020F</a>	20 mm	20 mm	Steel	Low Profile	40 mm	65 mm
<a href="#">5SM025025F</a>	25 mm	25 mm	Stainless Steel	Low Profile	45 mm	65 mm
<a href="#">5LM025025F</a>	25 mm	25 mm	Steel	Low Profile	45 mm	65 mm
<a href="#">5SM030030F</a>	30 mm	30 mm	Stainless Steel	Low Profile	54 mm	75 mm
<a href="#">5LM030030F</a>	30 mm	30 mm	Steel	Low Profile	54 mm	75 mm
<a href="#">5SM035035F</a>	35 mm	35 mm	Stainless Steel	Low Profile	57 mm	80 mm



**Stafford Manufacturing Corp.**

256 Andover St.  
Wilmington, MA 01887

**Phone:** 978.657.8000

**Fax:** 978.657.4731

For More Information:

800.695.5551

[sales@staffordmfg.com](mailto:sales@staffordmfg.com)