



Campane Femmina per GO-0A + GO-11A

No.2 ingrassatori G1/8" disposti a 180° su ogni campana per LUBRIFICAZIONE

Esecuzione con flange laterali asportabili disponibile a richiesta per grand. da 4 a 11 es. di designazione: GO-6A.C

TAB. 39

GRANDEZZA	Dimensioni flangia di accoppiamento [mm]							Coppia di Serraggio [Nm]
	D	S	^{H7} C	F	A	z	^{H8-d8} B	
0	111	12	80	3	96	6	8/M8	18
1	142	10	100	3	122	8	10/M10	36
2	168	10	122	3	148	10	10/M10	36
3	200	13	148	3	178	10	12/M12	65
4	225	13	172	3	203	12	12/M12	65
5	265	22	200	4	236	12	16/M16	150
6	300	22	232	4	270	14	16/M16	150
7	330	22	260	5	300	14	16/M16	150
8	370	24	286	5	335	14	18/M18	220
9	406	25	315	5	368	14	22/M22	400
10	438	25	345	5	400	14	22/M22	400
11	505	28	400	6	460	16	24/M24	520

TAB. 40

GRANDEZZA	Diam. Mozzo F	Foro max con 1 cava			Foro max con 2 cave			Fori Estrazione	
		max d	Linguetta bxh	max k	max d	Linguetta bxh	max k	No. 2 Fori a 180° G	M
		0	69	48	14x9	51.8	52	16x10	60.6
1	85	62	16x10	66.4	62	18x11	70.8	73	M6x20
2	107	72	20x12	76.9	78	22x14	88.8	91	M8x20
3	133	90	25x14	95.4	98	28x16	110.8	115	M10x20
4	152	105	28x16	111.4	112	32x18	126.8	132	M12x20
5	178	122	32x18	129.4	132	36x20	148.8	154	M12x20
6	209	144	36x20	152.4	156	40x22	174.8	180	M16x25
7	234	160	40x22	169.4	174	45x25	194.8	204	M16x25
8	254	175	45x25	185.4	190	45x25	210.8	220	M20x35
9	279	192	45x25	202.4	210	50x28	232.8	240	M20x35
10	305	210	50x28	221.4	233	56x32	257.8	268	M24x45
11	355	245	56x32	257.4	280	63x32	304.8	316	M24x45

Esecuzione a Richiesta
Esecuzione Standard

